



## 2780

Headlamp

Own the night with Main, Downcast, Flashing, and Main/Downcast Combo LED Modes. The Main LED illuminates everything in front, the Downcast LED illuminates everything below and, for an expanded view, switch to Main/Downcast Combo LED Mode. With 430 lumens of bright LED light, you'll conquer technical terrain without stumbling over dark, unseen obstacles. Plus, the flashing mode can be used as a beacon.

The new Pelican™ 2780 LED headlamp: You won't miss a thing.

- 4 AA Batteries Included
- 430 High Intensity Lumens
- Downcast LED Technology
- Includes 3 interchangeable Covers (Black, White, Photoluminescent)
- IPX7 Waterproof
- Pivoting Head For Directional Beam (60°)
- Includes Full Time Battery Status Indication



### DIMENSIONS

<b>Length</b>	3.00" (7.6 cm)
---------------	----------------

### MATERIALS

<b>Body</b>	Polycarbonate (PC)
<b>O-Ring</b>	Gasket
<b>Lens</b>	Polycarbonate (PC)
<b>Shroud</b>	Polycarbonate (PC)

### COLOURS

■ Black / White /  
Photoluminescent

### LIGHT SPECS

<b>Lamp Type</b>	LED
<b>Lamp Secondary Type</b>	LED

### POWER

<b>Battery Size</b>	AA
<b>Battery Type</b>	Alkaline
<b>Battery Quantity</b>	4
<b>Batteries Included</b>	yes
<b>Volts</b>	6.0v

### WEIGHT

<b>Weight With Batteries</b>	8.8 oz (249 gr)
<b>Weight Without Batteries</b>	6.6 oz (187 gr)

SWITCH

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
 Rotary / Push Button  
**Switch Type**  
**Light Modes** High / Medium / Low / Downcast / Spot / Flashing  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

Document created on 04-11-26

OTHER

**Minimum Pack** 1  
**Package Code** C

FL1 STANDARD	HIGH	MED	LOW	HIGH	MED	LOW	HIGH	MED	MED	HIGH
	234 LUMENS	109 LUMENS	28 LUMENS	430 LUMENS	203 LUMENS	53 LUMENS	216 LUMENS	101 LUMENS	26 LUMENS	216 LUMENS
	2h 30mins	5h 30mins	22h 0mins	1h 30mins	3h 0mins	12h 0mins	2h 15mins	5h 0mins	22h 0mins	h 0mins
	124m	81m	27m	124m	81m	27m	124m	81m	27m	124m
	3868cd	1625cd	425cd	3868cd	1625cd	425cd	3868cd	1625cd	425cd	3868cd
	1m									
	IPX7									

ACCESSORIES