



## 9415i

### 9410L + Safety = 9415i

#### Everything that's great about the 9410L LED Lantern, plus safety certificates

At just 1.4kg (3 pounds) and 530 lumens, the 9415i LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Ni-MH batteries illuminate a distance of 272 meters. And it's loaded with innovative technology and features you have come to expect from Pelican.

Safety certified for the most volatile work areas, the 9415i LED Lantern is safe and one of the most compact, high output lanterns on the market.




### DIMENSIONS

<b>Length</b>	8.75" (22.2 cm)
---------------	-----------------

### MATERIALS

<b>Body</b>	Anti-static Impact Modified PC/PBT
<b>O-Ring</b>	EPDM
<b>Lens</b>	Anti-static coated Polycarbonate (PC)
<b>Shroud</b>	Anti-static Impact Modified PC/PBT

### COLOURS

 High Visibility Yellow
--

### LIGHT SPECS

<b>Lamp Type</b>	LED
------------------	-----

### POWER

<b>Battery Size</b>	C
<b>Battery Type</b>	NiMH
<b>Battery Quantity</b>	4
<b>Batteries Included</b>	yes
<b>Rechargeable</b>	yes
<b>Charge Time</b>	15 hrs
<b>Battery Level Indicator</b>	RGB LED
<b>Volts</b>	4.8v

### WEIGHT

<b>Weight With Batteries</b>	58.2 oz (1650 gr)
<b>Weight Without Batteries</b>	0.0 oz (0 gr)

## SWITCH






<b>Switch Type</b>	Push Button
<b>Light Modes</b>	High / Low / Flashing

## CERTIFICATIONS

**IECEX ia**  
**ATEX Zone 0**

## OTHER

<b>Minimum Pack</b>	1
<b>Package Code</b>	B

FL1 STANDARD	HIGH	LOW
	530 LUMENS	202 LUMENS
	4h 30mins	11h 30mins
	272m	166m
	18480cd	6914cd
	IPX4	

## ACCESSORIES



**9416**

Deck/Dash Charger Base Unit



**6061F**

Direct Wiring Rig for Fast Charger



**8056F**

12v Plug-in for Fast Charger



**9418Z0**

Replacement Battery

---

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 04-10-26*