



## 3410MCC

Right Angle Light

When you can't see the difference between one color cable from another, the job may be compromised. Now you can trust our select flashlights with new Correct Color technology to stop the guess work.

Common LED lights can produce an intense beam and lower CRI (Color Rendering Index), making it difficult to distinguish between different color cables and overpower your work area with blinding bright light. Our new Correct Color flashlights are engineered with a higher CRI (90+ Color Rendering Index) allowing you to see color more accurately in your work environment. And with a low temperature beam (similar to incandescent flashlights) you get the benefits of our Correct Color technology that doesn't outshine the details.

- 3 Modes: High / Medium / Low
- 3 AA Alkaline Batteries (not included)
- Up to 155m Beam Distance
- Up to 484 Lumens
- Learn more about Correct Color Lights



### DIMENSIONS

<b>Length</b>	7.44" (18.9 cm)
---------------	-----------------

### MATERIALS

<b>Body</b>	Photo luminescent Polycarbonate (PC)
<b>O-Ring</b>	NBR
<b>Lens</b>	Clear Polycarbonate (PC)
<b>Shroud</b>	Photo luminescent Polycarbonate (PC)
<b>Clip</b>	Photo luminescent Polycarbonate (PC)
<b>Contact Spring Retainer</b>	Stainless Steel / Phosphore Bronze / Brass Nickel Plate

### COLOURS

 Photoluminescent

### LIGHT SPECS

<b>Lamp Type</b>	LED
<b>Lamp Secondary Type</b>	LED

### POWER






<b>Battery Size</b>	AA
<b>Battery Type</b>	Alkaline
<b>Battery Quantity</b>	3
<b>Volts</b>	4.5v

### WEIGHT

<b>Weight With Batteries</b>	9.2 oz (261 gr)
<b>Weight Without Batteries</b>	6.6 oz (187 gr)

## SWITCH

**Switch Type** Push Button  
**Light Modes** High / Medium / Low / Flashing

FL1 STANDARD	HIGH	MED	LOW	HIGH	MED	LOW	HIGH	MED	LOW
	272 LUMENS	62 LUMENS	16 LUMENS	314 LUMENS	68 LUMENS	18 LUMENS	484 LUMENS	64 LUMENS	17 LUMENS
	6h 0mins	21h 0mins	67h 0mins	5h 0mins	21h 0mins	64h 0mins	4h 0mins	20h 0mins	67h 0mins
	46m	21m	11m	161m	37m	37m	155m	56m	29m
	521cd	108cd	28cd	6471cd	339cd	339cd	5991cd	796cd	205cd
	IPX8 (1m)								

## ACCESSORIES



**2469P**  
Replacement Battery

### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

Document created on 07-10-26