



1440

Protector

Top Loader Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Retractable extension trolley handle
- Stainless steel padlock protectors
- Ultra-tough HPX[®] Polymer Construction



CONFIGURATIONS



1440
Standard



1444
With Utility Padded Divider Set & Lid Organizer



1447
With Padded Office Divider Set & Lid Organizer



1440NF
No Foam



1440WF
With Foam

DIMENSIONS

Interior (LxWxD)	17.10 x 7.50" x 16.00 (43.4 x 19.1 x 40.6 cm)
Exterior (LxWxD)	19.70 x 12.00" x 18.00 (50 x 30.5 x 45.7 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	14.00" (35.6 cm)
Total Depth	16" (40.6 cm)
Int Volume	1.19 ft ³ (0.034 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS

Purge Vent

3 Micron Hydrophobic Non-Woven

COLOURS

■ Black

WEIGHT

Weight With Foam	16.50 lbs (7.5 kg)
Weight Empty	14.50 lbs (6.6 kg)
Buoyancy	95.30 lbs (43.2 kg)
Master Pack Weight	18.00 lbs (8.2 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

CERTIFICATIONS

IP67
Def Stan 81-41

OTHER

Wheels	2
Extendable Handle	yes
Master Pack	1
Nameplate	yes

ACCESSORIES



1441
6 pc. Replacement Foam Set



1443
Replacement O-ring



1448
Photographer's Lid Organizer



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 07-10-26