



BS1610PEL108

Protector

Starlink Standard Actuated Case

The Pelican™ 1610 Protector Case offers military-grade protection for your Starlink Standard Actuated equipment. Designed with precision laser-cut, high-quality foam, it ensures a secure fit for your gear, while being watertight, dustproof, and crushproof for maximum durability.

With a retractable trolley handle, side handles, and smooth-rolling wheels, it's built for easy transport in the toughest conditions. Whether facing the freezing cold of the Arctic or the heat of the desert, Pelican cases are built to last and perform in the harshest conditions on Earth.

- Precision-cut foam inserts securely hold Starlink Standard Actuated equipment
- Watertight, dustproof, and crushproof for extreme environmental protection
- Military-grade materials for superior durability and protection
- Retractable extension trolley handle and fold-down side handles for easy transport
- Strong polyurethane wheels with stainless steel bearings for smooth mobility
- Designed to withstand harsh conditions, from arctic cold to intense heat
- 1610 Pelican Protector Case ensures secure transport and storage for vital equipment



DIMENSIONS

Interior (LxWxD)	21.78 x 16.69" x 10.62 (55.3 x 42.4 x 27 cm)
Exterior (LxWxD)	24.83 x 19.69" x 11.88 (63.1 x 50 x 30.2 cm)
Lid Depth	2.05" (5.2 cm)
Bottom Depth	8.57" (21.8 cm)
Total Depth	10.62" (27 cm)
Int Volume	2.23 ft ³ (0.063 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

■ Black

WEIGHT

Weight With Foam 23.15 lbs (10.5 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)

Maximum Temperature 190°F (87.8 °C)

OTHER

Wheels	2
Nameplate	yes

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 05-26-26