



2690

HeadsUp Lite™

Headlamp

Regardless of the season or environment, the 2690 HeadsUp Lite™ headlamp won't leave you in the dark. With 74 lumens of LED light, 11 hours of battery run time and weighing in at 4.1 ounces, it's brighter, more efficient, compact and lighter than other headlamps in its class. It's abundant safety approvals (Class I II III Division 1) allow for use in some of the most volatile of environments. The no-nonsense rotary bezel switch is easy to operate, even when wearing bulky gloves.

The 2690 is made of impact and chemical resistant ABS and it's water resistant for all-weather use. It comes with an adjustable and comfortable cloth strap, as well as a heavy duty rubber strap that will not slip off your climbing helmet or hard hat.

The 2690 HeadsUp Lite™ headlamp is engineered for those who take the outdoors seriously.

Use your head. Get the 2690 HeadsUp Lite™ headlamp from Pelican.

The 2690 is now IECEX underground mining approved.

- Built Pelican tough
- Hands-free design
- Cloth and Rubber Straps Included
- Class I, Class II, Class III - Division 1 Safety Certified



DIMENSIONS

Length	2.81" (7.1 cm)
---------------	----------------

MATERIALS

Body	ABS
O-Ring	EPDM
Lens	Polycarbonate (PC)
Shroud	ABS
Contact Spring Retainer	Nickel-Plated Phosphore Bronze

COLOURS

<input checked="" type="checkbox"/> Black

LIGHT SPECS

Lamp Type	LED
Lamp Life	10000 hrs

POWER

Battery Size	AAA
Battery Type	Alkaline
Battery Quantity	3
Batteries Included	yes
Volts	4.5v

WEIGHT

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
Weight With Batteries 4.1 oz (116 gr) sales@pelican.com • www.pelican.com
Weight Without Batteries 2.8 oz (79 gr)

Document created on 02-24-26

SWITCH

Switch Type One-handed Rotary Switch
Light Modes On / Off

CERTIFICATIONS

Class I, Division 1
Class II, Division 1
Class III, Division 1
IECEx ia

OTHER

Minimum Pack 1
Package Code C

FL1 STANDARD	HIGH
	74 LUMENS
	11h 0mins
	92m
	2124cd
	IPX7

ACCESSORIES