



## 1120 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware
- Ultra-tough HPX<sup>®</sup> Polymer Construction



## CONFIGURATIONS



**1120**  
Standard



**1120NF**  
No Foam



**1120WF**  
With Foam

## DIMENSIONS

|                              |  |
|------------------------------|--|
| <b>Interior (LxWxD)</b>      | 7.29 x 4.78" x 3.33 (18.5 x 12.1 x 8.5 cm)   |
| <b>Exterior (LxWxD)</b>      | 8.41 x 6.76" x 3.87 (21.4 x 17.2 x 9.8 cm)   |
| <b>Lid Depth</b>             | 0.50" (1.3 cm)                               |
| <b>Bottom Depth</b>          | 2.56" (6.5 cm)                               |
| <b>Total Depth</b>           | 3.06" (7.8 cm)                               |
| <b>Int Volume</b>            | 0.07 ft <sup>3</sup> (0.002 m <sup>3</sup> ) |
| <b>Padlock Hole Diameter</b> | 0.19" (0.5 cm)                               |

## MATERIALS

|                   |                                |
|-------------------|--------------------------------|
| <b>Body</b>       | Polypropylene                  |
| <b>Latch</b>      | Polypropylene                  |
| <b>O-Ring</b>     | Polymer                        |
| <b>Pins</b>       | Stainless Steel                |
| <b>Foam</b>       | 1.3 lb Polyurethane            |
| <b>Purge Body</b> | ABS                            |
| <b>Purge Vent</b> | 3 Micron Hydrophobic Non-Woven |

## COLOURS

■ Black  
■ Silver

■ Blue  
■ Yellow

■ Desert Tan

■ Orange

## WEIGHT

|                           |                    |
|---------------------------|--------------------|
| <b>Weight With Foam</b>   | 1.43 lbs (0.6 kg)  |
| <b>Weight Empty</b>       | 1.34 lbs (0.6 kg)  |
| <b>Master Pack Weight</b> | 10.45 lbs (4.7 kg) |

## TEMPERATURE

|                            |                 |
|----------------------------|-----------------|
| <b>Minimum Temperature</b> | -40°F (-40 °C)  |
| <b>Maximum Temperature</b> | 190°F (87.8 °C) |

## CERTIFICATIONS

**IP67**  
**Def Stan 81-41**

## OTHER

|                    |     |
|--------------------|-----|
| <b>Master Pack</b> | 6   |
| <b>Military</b>    | yes |

## ACCESSORIES



**1121**  
3 pc. Replacement Foam Set



**1123**  
Replacement O-ring



**1120PF**  
Special Application Panel Frame



**1120TPDIV**  
Extra TrekPak Dividers



**1120TPKIT**  
TrekPak Case Divider Kit



**1507QM**  
Quick Mounts - set of 4



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

Document created on 05-26-26