



1170 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **The hand-held electronics protection solution**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware
- Ultra-tough HPX® Polymer Construction



CONFIGURATIONS



1170
Standard



1170NF
No Foam



1170WF
With Foam

DIMENSIONS

Interior (LxWxD)	10.54 x 6.04" x 3.16 (26.8 x 15.3 x 8 cm)
Exterior (LxWxD)	11.64 x 8.34" x 3.78 (29.6 x 21.2 x 9.6 cm)
Lid Depth	1.08" (2.7 cm)
Bottom Depth	2.08" (5.3 cm)
Total Depth	3.16" (8 cm)
Int Volume	0.12 ft ³ (0.003 m ³)
Padlock Hole Diameter	0.19" (0.5 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	Polyurethane
Purge Body	ABS

Purge Vent

3 Micron Hydrophobic Non-Woven

COLOURS

- | | | | |
|--|--|--|---|
|  Black |  Desert Tan |  Orange |  OD Green |
|  Silver |  Yellow | | |

WEIGHT

- | | |
|---------------------------|--------------------|
| Weight With Foam | 2.10 lbs (1 kg) |
| Weight Empty | 1.96 lbs (0.9 kg) |
| Buoyancy | 7.25 lbs (3.3 kg) |
| Master Pack Weight | 12.79 lbs (5.8 kg) |

TEMPERATURE

- | | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 190°F (87.8 °C) |

CERTIFICATIONS

IP67

OTHER

Master Pack 6

ACCESSORIES



1171
3 pc. Replacement Foam Set



1173
Replacement O-ring



1507QM
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 05-26-26