



3410M

Right Angle Light

The most versatile pro-grade flashlight in the world, with magnet clip.

The 3410M (magnet version) is the ultimate compact work light. Molded from "glow in the dark" photoluminescent material, this light is easy to find even when it's off. The 3410M is equipped with both a spot and flood LED for close-up as well as distance, so you can have wide area light in the immediate work area and still penetrate darkness hundreds of yards away. It can be activated to run one or both LEDs with 3 levels of brightness. The articulating head and built-in clip allows the light to be directed wherever it is needed, while a heavy duty magnet allows the light to be snapped to steel surfaces. The Pelican 3410M- a professional grade multi-task lighting tool that will help you get the job done- under any circumstances.

- Articulating Light Head
- "Glow in the Dark" Body
- Attached clip with integrated magnet
- Security Lanyard
- 3 Modes: High / Medium / Low
- 4 modes: spot/flood, spot, flood, flashing
- Split ring installed



DIMENSIONS

| | |
|---------------|-----------------|
| Length | 7.44" (18.9 cm) |
|---------------|-----------------|

MATERIALS

| | |
|--------------------------------|---|
| Body | Photo luminescent Polycarbonate (PC) |
| O-Ring | NBR |
| Lens | Clear Polycarbonate (PC) |
| Shroud | Photo luminescent Polycarbonate (PC) |
| Clip | Photo luminescent Polycarbonate (PC) |
| Contact Spring Retainer | Stainless Steel / Phosphore Bronze / Brass Nickel Plate |

COLOURS

 Photoluminescent

LIGHT SPECS

| | |
|----------------------------|-----|
| Lamp Type | LED |
| Lamp Secondary Type | LED |

POWER

| | |
|-------------------------|----------|
| Battery Size | AA |
| Battery Type | Alkaline |
| Battery Quantity | 3 |
| Volts | 4.5v |

WEIGHT

| | |
|------------------------------|-----------------|
| Weight With Batteries | 9.9 oz (281 gr) |
|------------------------------|-----------------|

Weight Without Batteries

7.4 oz (210 gr)






SWITCH

Switch Type

Push Button

Light Modes

High / Medium / Low / Flashing

| FL1 STANDARD | HIGH | MED | LOW | HIGH | MED | LOW | HIGH | MED | LOW |
|---|------------|-----------|-----------|------------|-----------|-----------|------------|-----------|-----------|
|  | 404 LUMENS | 90 LUMENS | 23 LUMENS | 653 LUMENS | 97 LUMENS | 25 LUMENS | 441 LUMENS | 98 LUMENS | 25 LUMENS |
|  | 6h 0mins | 20h 0mins | 67h 0mins | 5h 0mins | 19h 0mins | 61h 0mins | 6h 0mins | 20h 0mins | 63h 0mins |
|  | 54m | 25m | 13m | 184m | 67m | 34m | 194m | 90m | 45m |
|  | 737cd | 161cd | 40cd | 8504cd | 1129cd | 292cd | 9408cd | 2019cd | 514cd |
|  | IPX8 (1m) | | | | | | | | |

ACCESSORIES



2469P

Replacement Battery

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com

Document created on 05-26-26