



1600 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Watertight, crushproof, and dustproof**
- 2 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors
- Ultra-tough HPX® Polymer Construction



CONFIGURATIONS



1600
Standard



1604
With Padded Dividers



1600NF
No Foam



1600TP
With TrekPak Divider System



1600WF
With Foam

DIMENSIONS

| | |
|------------------------------|--|
| Interior (LxWxD) | 21.51 x 16.54" x 7.99 (54.6 x 42 x 20.3 cm) |
| Exterior (LxWxD) | 24.39 x 19.36" x 8.79 (62 x 49.2 x 22.3 cm) |
| Lid Depth | 1.75" (4.4 cm) |
| Bottom Depth | 6.12" (15.5 cm) |
| Total Depth | 7.87" (20 cm) |
| Int Volume | 1.65 ft ³ (0.047 m ³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

MATERIALS


| | |
|-------------------|--------------------------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLOURS



Black

Yellow



Desert Tan



Orange



Silver

WEIGHT

| | |
|---------------------------|----------------------|
| Weight With Foam | 14.11 lbs (6.4 kg) |
| Weight Empty | 13.00 lbs (5.9 kg) |
| Buoyancy | 117.00 lbs (53.1 kg) |
| Master Pack Weight | 34.75 lbs (15.8 kg) |

TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 190°F (87.8 °C) |

CERTIFICATIONS

IP67
MIL C-4150J
Def Stan 81-41
ATA 300

OTHER

| | |
|--------------------|-----|
| Master Pack | 2 |
| Nameplate | yes |
| Military | yes |

ACCESSORIES



1601
4 pc. Replacement Foam Set



1602
Pick N Pluck™ Sections Only
(set of 2)



1603
Replacement O-ring



1605
Padded Divider Set



1609
Lid Organizer



1600TPKIT
TrekPak Case Divider Kit



1507QM
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 04-10-26