



1930 L1™

With a long lamp life and extended battery burn time, you won't be left in the dark with the L1™ flashlight. The polycarbonate body is resistant to chemicals, water and corrosion. The convenient tail switch for constant on/momentary is easy to operate. The L1™ is perfect for close quarter use. Packaged with 4 LR 44 1.5V alkaline coin cells, a break-a-way safety lanyard, and colored lens discs to preserve night vision. This handy flashlight offers a lot for its size.


- Built Pelican tough
- Super bright LED beam
- Unconditional Lifetime Guarantee of Excellence
- Security Lanyard



CONFIGURATIONS



1930
Standard



1930M
Merchandiser Display

DIMENSIONS

Length 2.64" (6.7 cm)

MATERIALS

Body	Polycarbonate (PC)
O-Ring	Ethylene Propylene
Lens	Polycarbonate (PC)
Shroud	Xenoy
Contact Spring Retainer	Phosphore Bronze

COLOURS

■ Black ■ High Visibility Yellow

LIGHT SPECS

Lamp Type LED

POWER

Battery Size LR 44

Battery Type Alkaline
Battery Quantity 4
Batteries Included yes
Volts 6.0v

WEIGHT

Weight With Batteries 0.9 oz (26 gr)
Weight Without Batteries 0.6 oz (17 gr)
Packaged Weight 0.8 oz (23 gr)

SWITCH


Switch Type Push Button Tail
Light Modes On / Off

CERTIFICATIONS

Class I, Division 1

OTHER

Minimum Pack 12
Military yes
Package Code C

FL1 STANDARD	HIGH
	13 LUMENS
	1h 30mins
	24m
	150cd
	IPX4

ACCESSORIES

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 04-10-26