



1670 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **4 strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 2 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- Two oversized fold down handles for extra grip



CONFIGURATIONS



1670
Standard



1670NF
No Foam



1670WF
With Foam



1674
With Padded Dividers

DIMENSIONS

| | |
|------------------------------|--|
| Interior (L×W×D) | 28.10 x 16.49" x 9.19 (71.4 x 41.9 x 23.3 cm) |
| Exterior (L×W×D) | 31.04 x 19.39" x 11.17 (78.8 x 49.3 x 28.4 cm) |
| Lid Depth | 1.80" (4.6 cm) |
| Bottom Depth | 7.39" (18.8 cm) |
| Total Depth | 9.19" (23.3 cm) |
| Int Volume | 2.46 ft ³ (0.07 m ³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

MATERIALS

| | |
|---------------|-----------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |

| | |
|-------------------|--------------------------------|
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLOURS

 Black

WEIGHT

| | |
|---------------------------|----------------------|
| Weight With Foam | 26.00 lbs (11.8 kg) |
| Weight Empty | 23.00 lbs (10.4 kg) |
| Buoyancy | 182.00 lbs (82.6 kg) |
| Master Pack Weight | 49.00 lbs (22.2 kg) |


TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 190°F (87.8 °C) |

OTHER

| | |
|--------------------|---|
| Wheels | 4 |
| Master Pack | 1 |

ACCESSORIES



1671
4 pc. Replacement Foam Set



1675
Padded Divider Set



1507QM
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 02-24-26