



AL2624-1805

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.


- Lignes de partage résistantes aux éclaboussures avec joints à rainure et languette moulés étroitement serrés en permanence, même
- Angles et bords renforcés pour protection additionnelle contre les impacts
- Épaulements et cannelures moulées pour empilement sûr et sans glissement, plus de force colonnaire et protection renforcée
- Matériel encastré pour une protection renforcée
- Verrous anti-tiraillement positif prévenant la séparation du couvercle après impact et réduisant les contraintes sur le matériel
- Inserts métalliques surmoulés brevetés aux points d'attache pour fermeture et charnière pour une meilleure résistance
- Construction monobloc, moulée à partir de polyéthylène léger résistant aux chocs



CONFIGURATIONS




AL2624-1805
Standard



AL2624-1805-RP
Empty



AL2624-1805RPC
No Foam, With Casters



AL2624-1805RPFC
With Foam, With Casters

DIMENSIONS

| | |
|-----------------------------|--|
| INTÉRIEUR | 26.06 x 24.00" x 22.87 (66.2 x 61 x 58.1 cm) |
| EXTÉRIEUR | 29.06 x 27.00" x 26.62 (73.8 x 68.6 x 67.6 cm) |
| profondeur couvercle | 5.06" (12.9 cm) |
| profondeur fond | 17.81" (45.2 cm) |
| profondeur totale | 22.87" (58.1 cm) |
| volume intérieur | 8.28 ft ³ (0.234 m ³) |

MATÉRIAUX

| | |
|-------------------------|--|
| corps | RotoMolded Polyethylene |
| loquet | Steel (Nickel-black Plated) |
| joint torique | Silicone Sponge |
| mousse | No Foam, empty case standard Optional PE and PU, 1 and 2 lb. options filled and lined |
| corps de purge | Aluminum |
| PRV Valve | .5 PSI Standard, Light Lift .25 PSI |
| poignée | Heavy Duty Injection Molded Standard |
| Optional Handles | Stainless Steel Passivate and Stainless Steel Black |

matériel

Yellow Carbon Steel Standard

Optional Hardware

Black Carbon Steel, Stainless Steel Passivate and Stainless Steel Black

COULEURS

■ Gray - 133 Fed Std
26270

POIDS

| | |
|---------------------------|-----------------------|
| poids | 38.50 lbs (17.5 kg) |
| flottabilité | 716.13 lbs (324.8 kg) |
| Master Pack Weight | 40.50 lbs (18.4 kg) |

TEMPÉRATURE

| | |
|-----------------------------|------------------|
| température minimale | -20°F (-28.9 °C) |
| température maximale | 140°F (60 °C) |

AUTRES

| | |
|--------------------------|-----|
| Domaine militaire | Oui |
|--------------------------|-----|

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 07-10-26