



2315

The hazard horizon is bright. With Class I, II, III - Division 1 and IECEx ia Safety Certification, 115 lumens and 75 meters of spot beam distance, the Pelican™ 2315 flashlight stretches light across dark, hazardous environments without being a source of ignition.

Engineered with an aluminum core and ABS overmolded plastic, these flashlights are built for rough handling and can survive hard drops. Plus, the sturdy clip attaches to a work vest for fast access and the tail switch activates raw LED power, even when using heavy-duty work gloves.

Pelican™ 2315 - SEE THE LIGHT AT THE END OF THE TUNNEL

- Construit selon les critères de résistance Pelican
- 2 piles alcalines AA (comprises)
- Clip intégré
- Interrupteur arrière d'activation momentanée/continue
- Class I, II, III - Division 1 / IECEx ia Safety Certified
- Étanchéité à l'eau IPX8 jusqu'à 1 m
- Montant de casque (inclus)




DIMENSIONS

longueur	6.22" (15.8 cm)
-----------------	-----------------

MATÉRIAUX

corps	ABS
joint torique	NBR
lentille	PC
revêtement	ABS
Pince	ABS

COULEURS

 High Visibility Yellow
--

LIGHT SPECS

type d'ampoule	LED
-----------------------	-----

POWER

taille des piles	AA
type de piles	Alkaline
nombre de piles	2
piles incluses	Oui
volts	3.0v

POIDS






poids avec piles	4.6 oz (130 gr)
poids sans piles	2.8 oz (79 gr)

SWITCH

type de commutateur Momentary Push Button
modes d'éclairage High

CERTIFICATIONS

Class I, Division 1
Class II, Division 1
Class III, Division 1
IECEX ia

FL1 STANDARD	HIGH
	115 LUMENS
	6h 0mins
	75m
	1403cd
	IPX8 (1m)

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 07-10-26