



## AL2825-1212

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.



### DIMENSIONS

---

|                             |  |
|-----------------------------|--|
| <b>INTÉRIEUR</b>            | 28.13 x 25.00" x 24.92 (71.5 x 63.5 x 63.3 cm) |
| <b>EXTÉRIEUR</b>            | 31.50 x 28.00" x 26.43 (80 x 71.1 x 67.1 cm)   |
| <b>profondeur couvercle</b> | 12.30" (31.2 cm)                               |
| <b>profondeur fond</b>      | 12.62" (32.1 cm)                               |
| <b>profondeur totale</b>    | 24.92" (63.3 cm)                               |
| <b>volume intérieur</b>     | 10.14 ft <sup>3</sup> (0.287 m <sup>3</sup> )  |

### MATÉRIAUX

---

|                          |  |
|--------------------------|--|
| <b>corps</b>             | RotoMolded Polyethylene  |
| <b>loquet</b>            | Steel (Nickel-black Plated)  |
| <b>joint torique</b>     | Silicone Sponge  |
| <b>mousse</b>            | No Foam, empty case standard<br>Optional PE and PU, 1 and 2 lb. options filled and lined |
| <b>corps de purge</b>    | Aluminum   |
| <b>PRV Valve</b>         | .5 PSI Standard, Light Lift .25 PSI  |
| <b>poignée</b>           | Heavy Duty Injection Molded Standard   |
| <b>Optional Handles</b>  | Stainless Steel Passivate and Stainless Steel Black                                      |
| <b>matériel</b>          | Yellow Carbon Steel Standard   |
| <b>Optional Hardware</b> | Black Carbon Steel, Stainless Steel Passivate and Stainless Steel Black                  |

### COULEURS

---

### POIDS

---

|              |                   |
|--------------|-------------------|
| <b>poids</b> | 44.00 lbs (20 kg) |
|--------------|-------------------|

### TEMPÉRATURE

---

|                             |                  |
|-----------------------------|------------------|
| <b>température minimale</b> | -20°F (-28.9 °C) |
| <b>température maximale</b> | 140°F (60 °C)    |

AUTRES

---

**Domaine militaire**

Oui

---

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 07-10-26*