



# 1510 Protector

Valise Carry-On

The original case introduced over 45 years ago has since evolved into the global standard for equipment protection. The Protector Case series is designed to survive and trusted to travel to the harshest environments on earth.

The Pelican 1510 Protector Case provides military-grade protection for a wide variety of gear, from camera equipment to camping kits. It is available with foam, without foam, padded dividers, or TrekPak dividers. The Pelican 1510 Protector Case is the maximum airline carry-on size, so you can travel with your sensitive gear close at hand.

(Check with your airline for exact measurement requirements)

- Maximum airline carry on size\*
- \* Check with your airline for exact measurement requirements.
- Watertight, crushproof, and dustproof
- Strong polyurethane wheels with stainless steel bearings
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Easy open double-throw latches
- Stainless steel hardware and padlock protectors
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- O-ring seal
- Lifetime Guarantee of Excellence
- Ultra-tough HPX<sup>®</sup> Polymer Construction



## CONFIGURATIONS



## DIMENSIONS

|                              |   |
|------------------------------|---|
| <b>INTÉRIEUR</b>             | 19.75 x 11.00" x 7.60 (50.2 x 27.9 x 19.3 cm) |
| <b>EXTÉRIEUR</b>             | 22.00 x 13.81" x 9.00 (55.9 x 35.1 x 22.9 cm) |
| <b>profondeur couvercle</b>  | 1.79" (4.5 cm)                                |
| <b>profondeur fond</b>       | 5.79" (14.7 cm)                               |
| <b>profondeur totale</b>     | 7.58" (19.3 cm)                               |
| <b>volume intérieur</b>      | 0.96 ft <sup>3</sup> (0.027 m <sup>3</sup> )  |
| <b>Padlock Hole Diameter</b> | 0.31" (0.8 cm)                                |

## MATÉRIAUX

|                       |                     |
|-----------------------|---------------------|
| <b>corps</b>          | Polypropylene       |
| <b>loquet</b>         | ABS                 |
| <b>joint torique</b>  | Polymer             |
| <b>broches</b>        | Stainless Steel     |
| <b>mousse</b>         | 1.3 lb Polyurethane |
| <b>corps de purge</b> | ABS                 |

**prise d'air de purge**

3 Micron Hydrophobic Non-Woven

## COULEURS

■ Black

■ Desert Tan

■ OD Green

## POIDS

|  |                     |
|--|---------------------|
| <b>poids avec mousse</b>                     | 13.60 lbs (6.2 kg)  |
| <b>poids sans mousse</b>                     | 11.99 lbs (5.4 kg)  |
| <b>flottabilité</b>                          | 64.15 lbs (29.1 kg) |
| <b>Weight With TrekPak /<br/>Foam Hybrid</b> | 14.94 lbs (6.8 kg)  |
| <b>Master Pack Weight</b>                    | 32.43 lbs (14.7 kg) |

## TEMPÉRATURE

|                             |                 |
|-----------------------------|-----------------|
| <b>température minimale</b> | -40°F (-40 °C)  |
| <b>température maximale</b> | 190°F (87.8 °C) |

## CERTIFICATIONS

**IP67**  
**Def Stan 81-41**

## AUTRES

|                            |     |
|----------------------------|-----|
| <b>roulettes</b>           | 2   |
| <b>Poignée extensible</b>  | Oui |
| <b>Pack Principal</b>      | 2   |
| <b>Plaques nominatives</b> | Oui |
| <b>Zone réduite</b>        | Oui |
| <b>Domaine militaire</b>   | Oui |

## ACCESSOIRES



**1511**  
Jeu de mousses de rechange,  
4 pièces



**1513**  
Joint torique de remplacement



**1515**  
Cloison en mousse



**1519**  
Pochette couvercle



**1510TPKIT**  
Kit de séparation de la valise  
TrekPak



**1507QM**  
Supports rapides - jeu de 4



**1506TSA**  
Serrure TSA



**1500D**  
Gel de silice dessicant



**1510MP**  
EZ-Click™ MOLLE Panel

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 07-10-26*