



## AL4532-1619

For over 65 years Pelican's roto-molded cases have been relied upon for an unmatched range of engineered solutions for the Military and Medical, Telecommunications and High Tech industries. Pelican offers over 350 case sizes with unlimited case configurations using standard case options. Either build your own case or our engineers will customize a solution specific to your performance requirements.

Our roto molded cases pass MIL-STD 810D and E, MIL-STD 810E MIL-STD-210C, ASTM E96; FED-STD-101 and ATA 300 testing.

This level of performance ensures your equipment is safe from any unforeseen elements when deploying, transporting or storing your most valuable assets.

- Hardware attaches to molded-in metal inserts to provide pull-out strength and load spreading so hardware never fails.
- Molded-in ribs and corrugations offer case strength for secure and heavy weight stacking capacity
- Recessed hardware, with its engineered shoulder geometry, reduces shear forces that prevents lid separation after impact and controls pressure on the gasket to maintain a weatherproof seal
- Angles et bords renforcés pour protection additionnelle contre les impacts
- Épaulements et cannelures moulées pour empilement sûr et sans glissement, plus de force colonnaire et protection renforcée
- Construction monobloc, moulée à partir de polyéthylène léger résistant aux chocs



### DIMENSIONS

|                             |   |
|-----------------------------|---|
| <b>INTÉRIEUR</b>            | 45.00 x 32.00" x 34.60 (114.3 x 81.3 x 87.9 cm) |
| <b>EXTÉRIEUR</b>            | 48.00 x 35.20" x 38.90 (121.9 x 89.4 x 98.8 cm) |
| <b>profondeur couvercle</b> | 19.00" (48.3 cm)                                |
| <b>profondeur fond</b>      | 15.60" (39.6 cm)                                |
| <b>profondeur totale</b>    | 34.6" (87.9 cm)                                 |
| <b>volume intérieur</b>     | 28.83 ft <sup>3</sup> (0.816 m <sup>3</sup> )   |

### MATÉRIAUX

|                          |  |
|--------------------------|--|
| <b>corps</b>             | RotoMolded Polyethylene  |
| <b>loquet</b>            | Steel (Nickel-black Plated)  |
| <b>joint torique</b>     | Silicone Sponge  |
| <b>mousse</b>            | No Foam, empty case standard<br>Optional PE and PU, 1 and 2 lb. options filled and lined |
| <b>corps de purge</b>    | Aluminum   |
| <b>PRV Valve</b>         | .5 PSI Standard, Light Lift .25 PSI  |
| <b>poignée</b>           | Heavy Duty Injection Molded Standard   |
| <b>Optional Handles</b>  | Stainless Steel Passivate and Stainless Steel Black                                      |
| <b>matériel</b>          | Yellow Carbon Steel Standard   |
| <b>Optional Hardware</b> | Black Carbon Steel, Stainless Steel Passivate and Stainless Steel Black                  |

### COULEURS

■ Gray - 133 Fed Std  
26270

### POIDS

**poids** 77.90 lbs (35.3 kg)

## TEMPÉRATURE

---

**température minimale** -20°F (-28.9 °C)

**température maximale** 140°F (60 °C)

## AUTRES

---

**Domaine militaire** Oui

---

### **Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 07-10-26*