



## iM2500

### Storm

Carry-On Case

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

The Pelican™ iM2500 Storm Case is designed to meet the maximum airline carry-on size, allowing you to keep your sensitive gear securely by your side while traveling. Be sure to verify the specific size requirements with your airline, as they may vary.

- Guaranteed for life
- **Watertight, crushproof, and dustproof**
- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin




## CONFIGURATIONS



**iM2500**  
Standard



**iM2500-X0000**  
No Foam



**iM2500-X0002**  
With Padded Dividers



**iM2500-X0006**  
With TrekPak Divider System



**iM2500-X0001**  
With Foam

## DIMENSIONS

<b>Interior (LxWxD)</b>	20.50 x 11.50" x 7.20 (52.1 x 29.2 x 18.3 cm)
<b>Exterior (LxWxD)</b>	21.70 x 14.10" x 8.90 (55.1 x 35.8 x 22.6 cm)
<b>Lid Depth</b>	2.00" (5.1 cm)
<b>Bottom Depth</b>	5.20" (13.2 cm)
<b>Total Depth</b>	7.2" (18.3 cm)
<b>Int Volume</b>	0.98 ft <sup>3</sup> (0.028 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	0.28" (0.7 cm)

## MATERIALS

<b>Body</b>	Injection Molded HPX™ high performance resin
<b>Latch</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Latch (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>O-Ring</b>	EPDM
<b>Pins</b>	Stainless Steel
<b>Pins (Alt)</b>	Aluminum
<b>Foam</b>	1.3/1.35 polyester
<b>Purge Body</b>	Valox - Polybutylene Terephthalate (PBT)

**Purge Body (Alt)** Xenoy - Polyester/Polycarbonate blend  
**Purge Vent** Gortex membrane

**COLORS**

■ Black      ■ OD Green      ■ Yellow

**WEIGHT**

**Weight With Foam** 13.70 lbs (6.2 kg)  
**Weight Empty** 11.10 lbs (5 kg)  
**Buoyancy** 62.56 lbs (28.4 kg)  
**Master Pack Weight** 42.10 lbs (19.1 kg)

**TEMPERATURE**

**Minimum Temperature** -20°F (-28.9 °C)  
**Maximum Temperature** 140°F (60 °C)


**CERTIFICATIONS**

**IP67**


**OTHER**

**Extendable Handle** yes  
**Master Pack** 3  
**Military** yes


**ACCESSORIES**



**iM2500-FOAM**  
5 pc. Replacement Foam Set



**iM2500-BEZEL-LID**  
Lid Bezel Kit



**iM2500-BEZEL**  
Base Bezel Kit



**iM-STRAP-S-VER2**  
Padded Shoulder Strap



**iM-LIDSTAY**  
Lid Stay




**iM2500TPKIT**  
TrekPak Case Divider Kit



**1555TPDIV**  
Extra TrekPak Dividers



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel



**22-IM-VALVE**  
Storm Case Automatic Purge Valve

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 05-26-26*