



iM3410

Storm

Long Case

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Five Press & Pull Latches
- Guaranteed For Life
- Four Padlockable Hasps
- Three Double-layered, Soft-grip Handles
- Powerful Hinges
- O-ring seal
- Lightweight Strong HPX® Resin



CONFIGURATIONS



iM3410
Standard



iM3410-X0000
No Foam



iM3410-X0001
With Foam

DIMENSIONS

Interior (L×W×D)	54.50 x 10.00" x 6.00 (138.4 x 25.4 x 15.2 cm)
Exterior (L×W×D)	57.74 x 12.71" x 6.67 (146.7 x 32.3 x 16.9 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	4.00" (10.2 cm)
Total Depth	6" (15.2 cm)
Int Volume	1.89 ft ³ (0.054 m ³)
Padlock Hole Diameter	0.37" (0.9 cm)

MATERIALS

Body	Injection Molded HPX™ high performance resin
Latch	Valox - Polybutylene Terephthalate (PBT)
Latch (Alt)	Xenoy - Polyester/Polycarbonate blend
O-Ring	EPDM
Pins	Stainless Steel
Pins (Alt)	Aluminum
Foam	1.3/1.35 polyester
Purge Body	Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt)	Xenoy - Polyester/Polycarbonate blend
Purge Vent	Gortex membrane

COLORS

■ Black

■ OD Green

WEIGHT

Weight With Foam 20.00 lbs (9.1 kg)

Weight Empty 18.00 lbs (8.2 kg)

TEMPERATURE

Minimum Temperature -20°F (-28.9 °C)

Maximum Temperature 140°F (60 °C)

CERTIFICATIONS

IP67

OTHER

Master Pack 1

Military yes

ACCESSORIES




iM3410-FOAM
4 pc. Replacement Foam Set



iM-LIDSTAY
Lid Stay



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



22-IM-VALVE
Storm Case Automatic Purge
Valve

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com

Document created on 05-26-26