



1460 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Also available with EMS Organizer and Dividers
- Personalized nameplate service available
- **Top lid opens up to 180° for on-the-field anti-roll stability when open**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handles
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors
- Ultra-tough HPX® Polymer Construction



CONFIGURATIONS



1460
Standard



1460AALG
With Custom Foam for 9430 / 9435



1460NF
No Foam



1460WF
With Foam

DIMENSIONS

Interior (LxWxD)	18.54 x 9.92" x 10.92 (47.1 x 25.2 x 27.7 cm)
Exterior (LxWxD)	20.85 x 12.73" x 12.75 (53 x 32.3 x 32.4 cm)
Lid Depth	4.91" (12.5 cm)
Bottom Depth	6.01" (15.3 cm)
Total Depth	10.92" (27.7 cm)
Int Volume	1.16 ft ³ (0.033 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	EXL
O-Ring	Polymer
Pins	Stainless Steel

Foam	Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLORS

■ Black

WEIGHT

Weight With Foam	12.48 lbs (5.7 kg)
Weight Empty	8.75 lbs (4 kg)
Buoyancy	82.00 lbs (37.2 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

CERTIFICATIONS

IP67

OTHER

Military yes

ACCESSORIES



1461
6 pc. Replacement Foam Set



1463
Replacement O-ring



1507QM
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 04-10-26