



3715

Right Angle Light

Pelican leads the way yet again with its new right angle light. Featuring downcast LEDs for illuminating your path, the new 3715 LED light also features 233 lumens (high) and 113 lumens (low), and a flashing mode. Another first is a built in battery life indicator so you will know your light's battery level before you go in. Compact, rugged, and lightweight, the 3715 LED light contains the latest technology, Pelican's legendary build quality and lifetime guarantee of excellence.

The new 3715 LED - Now you can **WATCH YOUR STEP.**

- 4 mode battery level indicating button
- Locking wheel securely holds 4 AA batteries
- Photoluminescent shroud (optional)
- Secure clip for hands-free use
- Tethered battery door allows for quick battery change
- **NOW WITH NEW UPGRADED SPECS**




DIMENSIONS

Length	5.36" (13.6 cm)
---------------	-----------------

MATERIALS

Body	ABS
O-Ring	Buna-N
Lens	Polycarbonate (PC)
Shroud	ABS
Clip	Xenoy

COLORS

 High Visibility Yellow

LIGHT SPECS

Lamp Type	LED
Lamp Secondary Type	LED

POWER

Battery Size	AA
Battery Type	Alkaline
Battery Quantity	4
Battery Level Indicator	3 Blue LEDs
Volts	6.0v

WEIGHT

Weight With Batteries	14.4 oz (408 gr)
Weight Without Batteries	11.0 oz (312 gr)

SWITCH






Switch Type	Push Button
Light Modes	High / Low / Downcast / Flashing

CERTIFICATIONS

IECEX ia
Class I, Division 1

OTHER

Minimum Pack	1
Package Code	B

FL1 STANDARD	HIGH	LOW	DOWNCAST
	233 LUMENS	113 LUMENS	31 LUMENS
	4h 0mins	7h 0mins	31h 0mins
	293m	187m	30m
	21440cd	8775cd	220cd
	IPX4		

ACCESSORIES



3713PL
Photoluminescent Shroud

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 05-26-26