



3765

Right Angle Light

- Compact and Lightweight
- NFPA Compliant (National Fire Protection Agency) 1901
- Also Operates on 4 Standard AA Alkaline Batteries
- **NOW WITH NEW UPGRADED SPECS**




DIMENSIONS

Length 5.36" (13.6 cm)

MATERIALS

Body ABS
O-Ring Buna-N
Lens Polycarbonate (PC)
Shroud ABS
Clip Xenoy

COLORS

 High Visibility Yellow

LIGHT SPECS

Lamp Type LED
Lamp Secondary Type LED

POWER

Battery Size AA
Battery Type NiMH
Battery Quantity 4
Batteries Included yes
Rechargeable yes
Charge Time 3 hrs 30 mins
Battery Level Indicator 3 Blue LEDs
Volts 4.8v

WEIGHT

Weight With Batteries 14.6 oz (414 gr)

Weight Without Batteries

11.0 oz (312 gr)

SWITCH

Switch Type

Push Button

Light Modes

High / Low / Downcast / Flashing

CERTIFICATIONS

Class I, Division 1

Class I, Division 2






OTHER

Minimum Pack

1

Package Code

B

FL1 STANDARD	HIGH	LOW	DOWNCAST	FLASHING
	237 LUMENS	113 LUMENS	32 LUMENS	140 LUMENS
	3h 0mins	6h 30mins	14h 0mins	9h 0mins
	301m	193m	28m	274m
	22720cd	9354cd	192cd	18784cd
	IPX4			

ACCESSORIES



2467F
110V Transformer (USA)



3713PL
Photoluminescent Shroud



3765FBC
Fast Charger Bank (5
receptacles)



3770F
Battery Charger Base



6061F
Direct Wiring Rig for Fast
Charger



8056F
12v Plug-in for Fast Charger



3769
Replacement Battery

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 07-10-26