



## 3765

Right Angle Light

- Compact and Lightweight
- NFPA Compliant (National Fire Protection Agency) 1901
- Also Operates on 4 Standard AA Alkaline Batteries
- **NOW WITH NEW UPGRADED SPECS**



### DIMENSIONS

<b>Length</b>	5.36" (13.6 cm)
---------------	-----------------

### MATERIALS

<b>Body</b>	ABS
<b>O-Ring</b>	Buna-N
<b>Lens</b>	Polycarbonate (PC)
<b>Shroud</b>	ABS
<b>Clip</b>	Xenoy

### COLORS

 High Visibility Yellow

### LIGHT SPECS

<b>Lamp Type</b>	LED
<b>Lamp Secondary Type</b>	LED

### POWER

<b>Battery Size</b>	AA
<b>Battery Type</b>	NiMH
<b>Battery Quantity</b>	4
<b>Batteries Included</b>	yes
<b>Rechargeable</b>	yes
<b>Charge Time</b>	3 hrs 30 mins
<b>Battery Level Indicator</b>	3 Blue LEDs
<b>Volts</b>	4.8v

### WEIGHT

<b>Weight With Batteries</b>	14.6 oz (414 gr)
------------------------------	------------------

**Weight Without Batteries**

11.0 oz (312 gr)

SWITCH

**Switch Type**

Push Button

**Light Modes**

High / Low / Downcast / Flashing

CERTIFICATIONS

**Class I, Division 1**

**Class I, Division 2**






OTHER

**Minimum Pack**

1

**Package Code**

B

FL1 STANDARD	HIGH	LOW	DOWNCAST	FLASHING
	237 LUMENS	113 LUMENS	32 LUMENS	140 LUMENS
	3h 0mins	6h 30mins	14h 0mins	9h 0mins
	301m	193m	28m	274m
	22720cd	9354cd	192cd	18784cd
	IPX4			

ACCESSORIES



**2467F**  
110V Transformer (USA)



**3713PL**  
Photoluminescent Shroud



**3765FBC**  
Fast Charger Bank (5  
receptacles)



**3770F**  
Battery Charger Base



**6061F**  
Direct Wiring Rig for Fast  
Charger



**8056F**  
12v Plug-in for Fast Charger



**3769**  
Replacement Battery

---

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 05-26-26*