

# 9430

Remote Area Lighting Systems from Pelican are the complete lighting solution for first responders, industrial and aerospace applications.

- Built Pelican tough
- New improved version Generation 3
- Up to 15 hours of run time
- 3000 lumens of brightness
- Fully extendable mast with 360 degree rotating head
- Low Battery Warning System
- Waterproof Rubber Activation Switch
- Mast Extension Lock
- RoHS and CE Compliant
- Includes 110 240 Volt (50/60hz) charger and universal adaptors



### **DIMENSIONS**

Head (L×W×D) 6.50 x 7.87" x 2.56 (16.5 x 20 x 6.5 cm)
Closed (L×W×D) 15.75 x 7.87" x 9.06 (40 x 20 x 23 cm)

**Light Head Height** 

(max)

32.28" (82 cm)

**Cord Length** 13.78" (35 cm)

### **MATERIALS**

BodyPolycarbonate (PC) / ABSHeadPolycarbonate (PC) / ABSMastGlass-Reinforced PlasticLensPolycarbonate (PC)

### **COLORS**

Black Yellow

### LIGHT SPECS

Lumens (High)3000Lumens (Low)1500Lamp Heads1Lamp TypeLEDNumber of LEDs6Beam Spread125°IP Rating54

#### **POWER**

**Run Time (High)** 8.00 hrs **Run Time (Low)** 15.00 hrs

Battery Type Sealed Lead Acid (SLA)

**Rechargeable** yes **Battery Lifespan** 500 cycles

Battery Level Indicator Intermittent Blinking

 Sockets (Primary)
 1

 Sockets (Aux)
 1

 Volts
 12.0v

## WEIGHT

**Weight** 22.65 lbs (10.3 kg)

### **SWITCH**

**Switch Type** Silicone Rubber Keypad

### **ACCESSORIES**



**1460AALG** 1460 Case with custom fit foam



**9430TP** Tripod



**9436B** 12/24V Vehicle Charger



**9437B**Extension Cord (black connector)
118in (3m)

#### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 11-21-25