



## 1460 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Also available with EMS Organizer and Dividers
- Personalized nameplate service available
- **Top lid opens up to 180° for on-the-field anti-roll stability when open**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handles
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors
- Ultra-tough HPX® Polymer Construction



### DIMENSIONS

<b>Interior (LxWxD)</b>	18.54 x 9.92" x 10.92 (47.1 x 25.2 x 27.7 cm)
<b>Exterior (LxWxD)</b>	20.85 x 12.73" x 12.75 (53 x 32.3 x 32.4 cm)
<b>Lid Depth</b>	4.91" (12.5 cm)
<b>Bottom Depth</b>	6.01" (15.3 cm)
<b>Total Depth</b>	10.92" (27.7 cm)
<b>Int Volume</b>	1.16 ft <sup>3</sup> (0.033 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	0.31" (0.8 cm)

### MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	EXL
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	Polyurethane
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	3 Micron Hydrophobic Non-Woven

### COLORS

- Black

### WEIGHT

<b>Weight With Foam</b>	12.48 lbs (5.7 kg)
<b>Weight Empty</b>	8.75 lbs (4 kg)
<b>Buoyancy</b>	82.00 lbs (37.2 kg)

## TEMPERATURE

---

**Minimum Temperature** -40°F (-40 °C)  
**Maximum Temperature** 190°F (87.8 °C)

## CERTIFICATIONS

---

**IP67**

## OTHER

---

**Military** yes

## ACCESSORIES

---



**1461**  
6 pc. Replacement Foam Set



**1463**  
Replacement O-ring



**PL2**  
Padlock (2 pack)



**1507QM**  
Quick Mounts - set of 4



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

---

### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

Document created on 04-10-26