



IS4521-2303

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.

- Removable Lid
- Freebreathing
- Black Carbon Steel, All Catch and Strike Hardware
- Colors: BLACK_032, GREY_133, OLIVE DRAB_137, RED_130, TAN_250
- Inter-Stacking Pattern Cases for NATO pallets, JMJC containers, 463L pallets or sea containers
- Hardware: Black Stainless Steel
- Pressure Relief Valve (PRV) with Closed Gasket
- Metal Handles: Black Stainless Steel
- 2 Cable Catch locks per case
- 2 Padlock Hasps per case
- 3" X 5" Horizontal Card Holder
- Front Labels, STD Labels and ATA Labels
- Pressure Relief Valve
- Humidity Indicator
- 8 Large Injection Molded Comfort Grip handles
- Lift Grip (750 lbs LC each installed)
- Skid Runners (4" height)



DIMENSIONS

Interior (LxWxD)	45.00 x 21.00" x 26.00 (114.3 x 53.3 x 66 cm)
Exterior (LxWxD)	48.00 x 24.00" x 32.00 (121.9 x 61 x 81.3 cm)
Lid Depth	3.00" (7.6 cm)
Bottom Depth	23.00" (58.4 cm)
Total Depth	26" (66 cm)
Int Volume	14.22 ft ³ (0.403 m ³)

MATERIALS

Body	RotoMolded Polyethylene
Latch	Steel (Nickel-black Plated)
O-Ring	Silicone Sponge
Foam	No Foam, empty case standard Optional PE and PU, 1 and 2 lb. options filled and lined
Purge Body	Aluminum
PRV Valve	.5 PSI Standard, Light Lift .25 PSI
Handle	Heavy Duty Injection Molded Standard
Optional Handles	Stainless Steel Passivate and Stainless Steel Black
Hardware	Yellow Carbon Steel Standard
Optional Hardware	Black Carbon Steel, Stainless Steel Passivate and Stainless Steel Black

COLORS

WEIGHT

Weight	72.00 lbs (32.7 kg)
---------------	---------------------

TEMPERATURE

Minimum Temperature -20°F (-28.9 °C)

Maximum Temperature 140°F (60 °C)

OTHER

Military yes

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 04-10-26