

# 1460EMS

#### **Protector**

**EMS** Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican  $^{\text{TM}}$  Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Also available without EMS Organizer and Dividers
- Personalized nameplate service available
- Lockable compartment for controlled substances
- Specifically designed in conjunction with Fire department and EMS personnel
- $\bullet$  Top lid opens up to 180° for on-the-field anti-roll stability when open
- Adjustable tray dividers allow for easy customization
- Automatic pressure equalization valve balances interior pressure, keeps water out
- $\bullet$  Each tray has an overall internal dimension of: 17" x 7.65" x 1.36" (43.18 x 19.43 x 3.45cm) LxWxD
- Easy open double-throw latches
- Lifetime Guarantee of Excellence (Tray system not covered by lifetime warranty)
- O-ring seal for dust and water resistant seal (IP66)
- · Open cell core with solid wall design strong, light weight
- Sharps storage bracket included
- Stainless steel hardware and padlock protectors
- \*Sharps container not included
- Each tray can support 1.5 lbs of weight



### **DIMENSIONS**

Interior (L×W×D) 18.54 x 9.92" x 10.92 (47.1 x 25.2 x 27.7 cm) Exterior (L×W×D) 20.85 x 12.73" x 12.75 (53 x 32.3 x 32.4 cm)

 Lid Depth
 4.91" (12.5 cm)

 Bottom Depth
 6.01" (15.3 cm)

 Total Depth
 10.92" (27.7 cm)

 Int Volume
 1.16 ft³ (0.033 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

#### **MATERIALS**

**Body** Polypropylene

LatchEXLO-RingPolymerPinsStainless SteelFoamPolyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

#### **COLORS**

Orange

### WEIGHT

Weight 18.20 lbs (8.3 kg)

### **TEMPERATURE**

**Minimum Temperature** -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

### **CERTIFICATIONS**

IP66

**NTOA Approved** 

# **OTHER**

Military

yes

# **ACCESSORIES**



1463 Replacement O-ring



**1466** Tray System for 1460EMS



**1506TSA** TSA Lock



**1500D** Desiccant Silica Gel



PL2 Padlock (2 pack)

#### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 11-21-25