

1510M

Protector

Mobility Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican $^{\text{\tiny TM}}$ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- \bullet 4" diameter x 1.5" wide (10.2 x 3.8cm) heavy duty polyurethane wheels with stainless steel bearings
- The Mobility Version of the 1510 Case is over the maximum FAA carry on size
- Water resistant, crushproof, and dust resistant
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- * Check with your airline for exact measurement requirements.



DIMENSIONS

Interior (L×W×D) 19.75 x 11.00" x 7.60 (50.2 x 27.9 x 19.3 cm) Exterior (L×W×D) 23.55 x 14.36" x 10.62 (59.8 x 36.5 x 27 cm)

 Lid Depth
 1.79" (4.5 cm)

 Bottom Depth
 5.79" (14.7 cm)

 Total Depth
 7.58" (19.3 cm)

 Int Volume
 0.96 ft³ (0.027 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLORS



WEIGHT

Weight With Foam 17.91 lbs (8.1 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

CERTIFICATIONS

IP57

OTHER

Wheels 2
Extendable Handle yes
Master Pack 1
Nameplate yes
Reduced Area yes
Military yes

ACCESSORIES



Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 11-21-25