

1560SC

Protector

Studio Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican $^{\text{\tiny TM}}$ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Padded removable sleeve for 15"-17" laptop computers
- Strong polyurethane wheels with stainless steel bearings
- · Three removable accessory pouches
- · Watertight, crushproof, and dustproof
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- · O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- This case may qualify as carry-on luggage on some airlines, check with your airline for more details



DIMENSIONS

 Interior (L×W×D)
 19.92 x 14.98" x 9.00 (50.6 x 38 x 22.9 cm)

 Exterior (L×W×D)
 22.07 x 17.92" x 10.42 (56.1 x 45.5 x 26.5 cm)

 Lid Depth
 2.00" (5.1 cm)

 Bottom Depth
 7.00" (17.8 cm)

 Total Depth
 9" (22.9 cm)

 Int Volume
 1.55 ft³ (0.044 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLORS

Black

WEIGHT

Weight With Foam 18.18 lbs (8.2 kg)
Weight Empty 17.00 lbs (7.7 kg)

Buoyancy 115.00 lbs (52.2 kg) **Master Pack Weight** 21.00 lbs (9.5 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

CERTIFICATIONS

IP67

Def Stan 81-41

OTHER

Wheels 2
Extendable Handle yes
Master Pack 1
Nameplate yes
Military yes

ACCESSORIES



0343Replacement O-ring



1506TSA TSA Lock



1500D Desiccant Silica Gel



PL2 Padlock (2 pack)

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 11-21-25