

1150

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

· Watertight, crushproof, and dustproof

- Automatic pressure equalization valve balances interior pressure, keeps water out
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck[™] with convoluted lid foam
- Stainless steel hardware



DIMENSIONS

Interior (L×W×D) 8.29 x 5.79" x 3.75 (21.1 x 14.7 x 9.5 cm) Exterior (L×W×D) 9.44 x 7.80" x 4.29 (24 x 19.8 x 10.9 cm)

 Lid Depth
 0.75" (1.9 cm)

 Bottom Depth
 2.87" (7.3 cm)

 Total Depth
 3.62" (9.2 cm)

 Int Volume
 0.1 ft³ (0.003 m³)

 Padlock Hole Diameter
 0.19" (0.5 cm)

MATERIALS

BodyPolypropyleneLatchPolypropyleneO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLORS

Black Blue Desert Tan Orange
Silver Yellow

WEIGHT

 Weight With Foam
 1.75 lbs (0.8 kg)

 Weight Empty
 1.61 lbs (0.7 kg)

 Buoyancy
 8.00 lbs (3.6 kg)

 Master Pack Weight
 13.95 lbs (6.3 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

CERTIFICATIONS

IP67

Def Stan 81-41

OTHER

Master Pack6Militaryyes

ACCESSORIES







1153 Replacement O-ring



1150PF Special Application Panel Frame



1150TPKIT TrekPak Case Divider Kit



1150TPDIV Extra TrekPak Dividers



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 11-21-25