



IS4537-2303

Confiados durante más de 40 años por el ejército de los EE. UU., Los cases de una sola tapa ofrecen un 20% más de material protector en los bordes y esquinas, donde más se necesita, asegurando que el valioso equipo se mantenga a salvo de cualquier elemento imprevisto. Disponibles en varios tamaños, estos cases son completamente personalizables con una amplia gama de opciones atornilladas como porta documentos, ruedas, indicadores de humedad y mucho más.

- Removable Lid
- Freebreathing
- Black Carbon Steel, All Catch and Strike Hardware
- Inter-Stacking Pattern Cases for NATO pallets, JMIC containers, 463L pallets or sea containers
- Hardware: Black Stainless Steel
- Pressure Relief Valve (PRV) with Closed Gasket
- Metal Handles: Black Stainless Steel
- 2 Cable Catch locks per case
- 3" X 5" Horizontal Card Holder
- Front Labels, STD Labels and ATA Labels
- Pressure Relief Valve
- Humidity Indicator
- 8 Large Injection Molded Comfort Grip handles
- Lift Grip (750 lbs LC each installed)
- Skid Runners (4" height)



DIMENSIONES

INTERIOR	45.00 x 37.00" x 26.00 (114.3 x 94 x 66 cm)
EXTERIOR	48.00 x 40.00" x 32.00 (121.9 x 101.6 x 81.3 cm)
profundidad tapa	3.00" (7.6 cm)
profundidad base	23.00" (58.4 cm)
profundidad total	26" (66 cm)
volumen interior	25.05 ft ³ (0.709 m ³)

MATERIALES

cuerpo	RotoMolded Polyethylene
cierre	Steel (Nickel-black Plated)
anillo de sellado de neopreno	Silicone Sponge
espuma	No Foam, empty case standard Optional PE and PU, 1 and 2 lb. options filled and lined
cuerpo de compensación	Aluminum
PRV Valve	.5 PSI Standard, Light Lift .25 PSI
asa	Heavy Duty Injection Molded Standard
Optional Handles	Stainless Steel Passivate and Stainless Steel Black
componentes metálicos	Yellow Carbon Steel Standard
Optional Hardware	Black Carbon Steel, Stainless Steel Passivate and Stainless Steel Black

COLORES

PESO

peso 93.00 lbs (42.2 kg)

LA TEMPERATURA

temperatura mínima -20°F (-28.9 °C)

temperatura máxima 140°F (60 °C)

OTRAS

Aplicaciones militares sí

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 04-11-26