



2780R

Headlamp

The most powerful headlamp in the Pelican™ line is now available! Meet the 2780R. With 676 lumens of brilliant light, USB lithium ion rechargeable battery along with a host of features, the 2780R makes for one of the most intriguing headlamps. The easy grip dial provides selection of the Main LED which illuminates everything in front with a beam distance of 139 meters, the Downcast LED illuminates everything below in a wide diffused pattern providing safe pathways, illuminated reading spaces and allowing for non-blinding face to face conversations, both beams combined, or a helpful flashing mode round out the forward light outputs. The easy grip dial also incorporates a push to select High / Medium / Low settings. Additional features offered in the 2780R are a unique rear mounted battery pack that provides full time battery level indication, charging levels and a rear mounted red LED safety light.

The Pelican™ 2780R Rechargeable LED Headlamp: The very best in hands free lighting.

- Downcast LED Technology
- Includes 3 interchangeable Covers (Black, White, Photoluminescent)
- 676 High Intensity Lumens
- USB Lithium Ion Rechargeable
- Rear Mounted Red LED
- Pivoting Head
- Comfortable Cloth Strap
- Includes Full Time Battery Status Indication



DIMENSIONS

Length	3.00" (7.6 cm)
---------------	----------------

MATERIALS

Body	Polycarbonate (PC)
O-Ring	Gasket
Lens	Polycarbonate (PC)
Shroud	Polycarbonate (PC)

COLORS

■ Black / White /
Photoluminescent

LIGHT SPECS

Lamp Type	LED
Lamp Secondary Type	LED

POWER

Battery Size	18650
Battery Type	Lithium-Ion
Battery Quantity	1
Batteries Included	yes
Rechargeable	yes
Charge Time	6 hrs

Battery Level Indicator 3 Blue LEDs
Volts 3.7v

WEIGHT






Weight With Batteries 7.3 oz (207 gr)
Weight Without Batteries 5.6 oz (159 gr)

SWITCH

Switch Type Rotary / Push Button
Light Modes High / Medium / Low / Downcast / Spot / Flashing

OTHER

Minimum Pack 1
Package Code C

FL1 STANDARD	HIGH	MED	LOW	HIGH	MED	LOW	HIGH	MED	LOW	HIGH
	397 LUMENS	185 LUMENS	92 LUMENS	676 LUMENS	252 LUMENS	118 LUMENS	414 LUMENS	187 LUMENS	93 LUMENS	333 LUMENS
	4h 30mins	6h 0mins	13h 0mins	2h 30mins	4h 15mins	10h 0mins	4h 30mins	5h 45mins	13h 0mins	h 0mins
	139m	93m	65m	139m	93m	65m	139m	93m	65m	139m
	4824cd	2158cd	1051cd	4824cd	2158cd	1051cd	4824cd	2158cd	1051cd	4824cd
	IPX7									

ACCESSORIES



2389
Replacement Battery

Document created on 07-10-26