



# iM2435

## Storm

Top Loader Case

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Guaranteed for life
- **Watertight, crushproof, and dustproof**
- Retractable extension trolley handle
- Two Press & Pull Latches
- In-line Wheels
- O-ring seal
- Lightweight Strong HPX® Resin
- Two stainless steel padlock protectors



### CONFIGURATIONS



**iM2435**  
Standard



**iM2435-X0000**  
No Foam



**iM2435-X0002**  
With Padded Dividers & Lid Organizer



**iM2435-X0001**  
With Foam

### DIMENSIONS

|                              |   |
|------------------------------|---|
| <b>Interior (LxWxD)</b>      | 17.50 x 6.50" x 15.50 (44.5 x 16.5 x 39.4 cm) |
| <b>Exterior (LxWxD)</b>      | 18.63 x 9.25" x 16.50 (47.3 x 23.5 x 41.9 cm) |
| <b>Lid Depth</b>             | 2.00" (5.1 cm)                                |
| <b>Bottom Depth</b>          | 13.50" (34.3 cm)                              |
| <b>Total Depth</b>           | 15.5" (39.4 cm)                               |
| <b>Int Volume</b>            | 1.02 ft <sup>3</sup> (0.029 m <sup>3</sup> )  |
| <b>Padlock Hole Diameter</b> | 0.37" (0.9 cm)                                |

### MATERIALS

|                         |  |
|-------------------------|--|
| <b>Body</b>             | Injection Molded HPX™ high performance resin |
| <b>Latch</b>            | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Latch (Alt)</b>      | Xenoy - Polyester/Polycarbonate blend        |
| <b>O-Ring</b>           | EPDM   |
| <b>Pins</b>             | Stainless Steel                              |
| <b>Pins (Alt)</b>       | Aluminum                                     |
| <b>Foam</b>             | 1.3/1.35 polyester                           |
| <b>Purge Body</b>       | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Purge Body (Alt)</b> | Xenoy - Polyester/Polycarbonate blend        |

**Purge Vent**

Gortex membrane

## COLORS

 Black

## WEIGHT

|                         |                     |
|-------------------------|---------------------|
| <b>Weight With Foam</b> | 11.15 lbs (5.1 kg)  |
| <b>Weight Empty</b>     | 10.00 lbs (4.5 kg)  |
| <b>Buoyancy</b>         | 56.70 lbs (25.7 kg) |

## TEMPERATURE

|                            |                  |
|----------------------------|------------------|
| <b>Minimum Temperature</b> | -20°F (-28.9 °C) |
| <b>Maximum Temperature</b> | 140°F (60 °C)    |

## CERTIFICATIONS

**IP67**

## OTHER

|                          |     |
|--------------------------|-----|
| <b>Extendable Handle</b> | yes |
| <b>Master Pack</b>       | 1   |
| <b>Military</b>          | yes |

## ACCESSORIES



**iM2435-FOAM**  
8 pc. Replacement Foam Set



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel



**22-IM-VALVE**  
Storm Case Automatic Purge Valve

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

Document created on 07-10-26