



# 1780RF

## Protector

Rifle Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Fits M4, M16 firearms**
- **Watertight, crushproof, and dustproof**
- Detachable halves serve as mobile firearm racks
- Fast loading, lockable metal cross bar
- Humidity gauge changes color above 40%
- Lifetime Guarantee of Excellence
- Manual Pressure Equalization Valve
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Made in the USA
- 4 heavy duty polyurethane wheels with stainless steel bearings for one-man mobility
- Hi-density foam tray option for 10 firearms
- Ultra-tough HPX<sup>®</sup> Polymer Construction



### DIMENSIONS

<b>Interior (LxWxD)</b>	41.12 x 21.54" x 14.88 (104.4 x 54.7 x 37.8 cm)
<b>Exterior (LxWxD)</b>	44.90 x 25.32" x 16.50 (114 x 64.3 x 41.9 cm)
<b>Lid Depth</b>	7.58" (19.3 cm)
<b>Bottom Depth</b>	7.30" (18.5 cm)
<b>Total Depth</b>	14.88" (37.8 cm)
<b>Int Volume</b>	7.63 ft <sup>3</sup> (0.216 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	5/16" (12.7 cm)

### MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	EXL
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.3 lb Polyurethane

### COLORS

■ Black

### TEMPERATURE

<b>Minimum Temperature</b>	-40°F (-40 °C)
<b>Maximum Temperature</b>	190°F (87.8 °C)

## OTHER

---

<b>Wheels</b>	4
<b>Master Pack</b>	1
<b>Nameplate</b>	yes

---

### **Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 04-08-26*