



## 1200 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Ultra-tough HPX<sup>®</sup> Polymer Construction



### CONFIGURATIONS



**1200**  
Standard



**1200WF**  
With Foam



**1200NF**  
No Foam

### DIMENSIONS

<b>Interior (LxWxD)</b>	9.31 x 7.13" x 4.12 (23.6 x 18.1 x 10.5 cm)
<b>Exterior (LxWxD)</b>	10.67 x 9.75" x 4.86 (27.1 x 24.8 x 12.3 cm)
<b>Lid Depth</b>	1.19" (3 cm)
<b>Bottom Depth</b>	2.93" (7.4 cm)
<b>Total Depth</b>	4.12" (10.5 cm)
<b>Int Volume</b>	0.16 ft <sup>3</sup> (0.005 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	0.19" (0.5 cm)

### MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	ABS
<b>O-Ring</b>	EDPM Medium Density
<b>Pins</b>	Stainless Steel
<b>Foam</b>	Polyurethane
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	LM10411

## COLORS

---

■ Black  
■ Silver

■ Desert Tan  
■ Yellow

■ Orange

■ OD Green

## WEIGHT

---

**Weight With Foam** 2.75 lbs (1.2 kg)  
**Weight Empty** 2.55 lbs (1.2 kg)  
**Buoyancy** 13.80 lbs (6.3 kg)  
**Master Pack Weight** 19.00 lbs (8.6 kg)

## TEMPERATURE

---

**Minimum Temperature** -40°F (-40 °C)  
**Maximum Temperature** 190°F (87.8 °C)

## OTHER

---

**Master Pack** 6  
**Military** yes

---

### **Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 05-26-26*