



1300 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Ultra-tough HPX[®] Polymer Construction



CONFIGURATIONS



1300
Standard

1300WF
With Foam

1300NF
No Foam

DIMENSIONS

Interior (LxWxD)	9.17 x 6.99" x 6.15 (23.3 x 17.8 x 15.6 cm)
Exterior (LxWxD)	10.70 x 9.76" x 6.89 (27.2 x 24.8 x 17.5 cm)
Lid Depth	1.19" (3 cm)
Bottom Depth	4.96" (12.6 cm)
Total Depth	6.15" (15.6 cm)
Int Volume	0.23 ft ³ (0.007 m ³)
Padlock Hole Diameter	0.19" (0.5 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	EDPM Medium Density
Pins	Stainless Steel
Foam	Polyurethane
Purge Body	ABS
Purge Vent	LM10411

COLORS

 Black	 Orange	 OD Green	 Silver
 Yellow			

WEIGHT

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
Weight With Foam 3.30 lbs (1.5 kg) sales@pelican.com • www.pelican.com
Weight Empty 3.10 lbs (1.4 kg)
Buoyancy 18.50 lbs (8.4 kg) *Document created on 05-26-26*
Master Pack Weight 17.00 lbs (7.7 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 190°F (87.8 °C)

OTHER

Master Pack 4
Military yes

ACCESSORIES
