



IS4537-2303

ISP Case

Shifting loose cargo can slow down your ops and threaten the mission with damaged freight. The new ISP Case from Pelican™ virtually eliminates load movement with a unique Inter-Stacking Pattern (ISP). The patent pending system is compatible across 6 different case sizes from 4 to 25 cubic feet of storage. Equipped with a silicone sponge O-ring and pressure release valves, the ISP Case is impervious to extreme weather and wet conditions.

The system is designed to maximize the volume of standard logistics platforms. Whether loading standard pallets, NATO pallets, JMJC containers, 463L pallets or sea containers, the ISP Case system will make the most efficient use of cargo space.

With its Inter-Stacking Pattern there is no question where the next case belongs. The disc pattern bottom mates with the wave pattern on the case below, literally falling and locking into place. Cross-stacking builds incredibly tight loads that can save time with strapping or netting.


- Standard Features:
 - Removable Lid
 - Freebreathing
 - Black Carbon Steel, All Catch and Strike Hardware
 - 8 Large Injection Molded Comfort Grip handles
 - Inter-Stacking Pattern Cases for NATO pallets, JMJC containers, 463L pallets or sea containers
- Configurable Features:
 - Hardware: Black Stainless Steel
 - Pressure Relief Valve (PRV) with Closed Gasket
 - Metal Handles: Black Stainless Steel
 - 2 Cable Catch locks per case
 - 3" X 5" Horizontal Card Holder
 - Front Labels, STD Labels and ATA Labels
 - Pressure Relief Valve
 - Humidity Indicator
 - Lift Grip (750 lbs LC each installed)
 - Skid Runners (4" height)



CONFIGURATIONS



IS4537-2303
Standard



IS4537-2303-No-Foam
No Foam

DIMENSIONS

Interior (LxWxD)	45.00 x 37.00" x 26.00 (114.3 x 94 x 66 cm)
Exterior (LxWxD)	48.00 x 40.00" x 32.00 (121.9 x 101.6 x 81.3 cm)
Lid Depth	3.00" (7.6 cm)
Bottom Depth	23.00" (58.4 cm)

Total Depth 26" (66 cm)
Int Volume 25.05 ft³ (0.709 m³)

MATERIALS

Body RotoMolded Polyethylene
Latch Steel (Nickel-black Plated)
O-Ring Silicone Sponge
Pins Stainless Steel
Pins (Alt) Aluminum
Purge Body Aluminum

COLORS

■ Black - 032 Fed Std 27040 ■ Olive Drab - 137 Fed Std 34096 ■ Gray - 133 Fed Std 26270 ■ Tan - 250 Fed Std 20372
■ Red - 130 Fed Std 21105

WEIGHT

Weight With Foam 148.00 lbs (67.1 kg)
Weight Empty 93.00 lbs (42.2 kg)

TEMPERATURE

Minimum Temperature -20°F (-28.9 °C)
Maximum Temperature 140°F (60 °C)

CERTIFICATIONS

MIL-STD-810F

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 07-10-26