



1520 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware and padlock protectors
- Ultra-tough HPX[®] Polymer Construction



CONFIGURATIONS



1520
Standard



1524
With Padded Dividers



1526
With Convertible Travel Bag



1520NF
No Foam



1520WF
With Foam

DIMENSIONS

Interior (LxWxD)	18.06 x 12.89" x 6.72 (45.9 x 32.7 x 17.1 cm)
Exterior (LxWxD)	19.78 x 15.77" x 7.41 (50.2 x 40.1 x 18.8 cm)
Lid Depth	1.79" (4.5 cm)
Bottom Depth	4.93" (12.5 cm)
Total Depth	6.72" (17.1 cm)
Int Volume	0.91 ft ³ (0.026 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLORS



Black

Yellow



Desert Tan



Orange



Silver

WEIGHT

Weight With Foam	9.35 lbs (4.2 kg)
Weight Empty	8.29 lbs (3.8 kg)
Buoyancy	63.00 lbs (28.6 kg)
Master Pack Weight	23.30 lbs (10.6 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

CERTIFICATIONS

IP67
MIL C-4150J
Def Stan 81-41

OTHER

Master Pack	2
Nameplate	yes
Military	yes

ACCESSORIES



1508
Photographer's Lid Organizer



1509
Lid Organizer



1521
3 pc. Replacement Foam Set



1523
Replacement O-ring



1525
Padded Divider Set



1520TPKIT
TrekPak Case Divider Kit



1520TPDIV
Extra TrekPak Dividers



1507QM
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1520PF
Special Application Panel
Frame

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 04-08-26