



472-PWC-M32

Mobile Armory™

Grenade Launcher Case

- Six Press & Pull Latches
- Two Double-layered, Soft-grip Handles
- Two Padlockable Hasps
- In-line Wheels
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX™ Resin
- Watertight
- Guaranteed For Life



DIMENSIONS

| | |
|-------------------------|--|
| Interior (L×W×D) | 44.00 x 14.00" x 8.50 (111.8 x 35.6 x 21.6 cm) |
| Exterior (L×W×D) | 47.20 x 16.50" x 9.20 (119.9 x 41.9 x 23.4 cm) |
| Lid Depth | 2.00" (5.1 cm) |
| Bottom Depth | 6.50" (16.5 cm) |
| Total Depth | 8.5" (21.6 cm) |
| Int Volume | 3.03 ft ³ (0.086 m ³) |

MATERIALS

| | |
|-------------------------|--|
| Body | Injection Molded HPX™ high performance resin |
| Latch | Valox - Polybutylene Terephthalate (PBT) |
| Latch (Alt) | Xenoy - Polyester/Polycarbonate blend |
| O-Ring | Silicone Sponge |
| Pins | Stainless Steel |
| Foam | 1.3/1.35 polyester |
| Purge Body | Valox - Polybutylene Terephthalate (PBT) |
| Purge Body (Alt) | Xenoy - Polyester/Polycarbonate blend |
| Purge Vent | Gortex membrane |

COLORS

| | |
|---|--|
|  Black |  OD Green |
|---|--|

WEIGHT

| | |
|---------------|---------------------|
| Weight | 24.80 lbs (11.2 kg) |
|---------------|---------------------|

TEMPERATURE

| | |
|----------------------------|------------------|
| Minimum Temperature | -20°F (-28.9 °C) |
| Maximum Temperature | 140°F (60 °C) |

OTHER

| | |
|---------------|---|
| Wheels | 2 |
|---------------|---|

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 07-10-26